

Package: glam (via r-universe)

September 9, 2024

Title Generalized Additive and Linear Models (GLAM)

Version 1.0.2

Description Contains methods for fitting Generalized Linear Models (GLMs) and Generalized Additive Models (GAMs). Generalized regression models are common methods for handling data for which assuming Gaussian-distributed errors is not appropriate. For instance, if the response of interest is binary, count, or proportion data, one can instead model the expectation of the response based on an appropriate data-generating distribution. This package provides methods for fitting GLMs and GAMs under Beta regression, Poisson regression, Gamma regression, and Binomial regression (currently GLM only) settings. Models are fit using local scoring algorithms described in Hastie and Tibshirani (1990) <doi:10.1214/ss/1177013604>.

License MIT + file LICENSE

Encoding UTF-8

Imports gam, stats

RoxygenNote 7.3.1

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Andrew Cooper [aut, cre, cph]

Maintainer Andrew Cooper <ahcooper@vt.edu>

Date/Publication 2024-07-09 15:40:02 UTC

Repository <https://andrewdjac.r-universe.dev>

RemoteUrl <https://github.com/cran/glam>

RemoteRef HEAD

RemoteSha 9d00c16b3530930c15cad24126ac5a8b30473de3

Contents

| | |
|----------------|----------|
| glam | 2 |
| Index | 4 |

| | |
|------|---|
| glam | <i>Generalized Linear/Additive Model (GLAM)</i> |
|------|---|

Description

glam fits Generalized Linear Models (GLMs) and Generalized Additive Models (GAMs).

Usage

```
glam(x, y, model, family, intercept = TRUE, tol = 1e-08, max_iter = 100)
```

Arguments

| | |
|-----------|--|
| x | a matrix with covariate data. |
| y | a vector of responses. |
| model | a string stating whether a GLM ("linear") or GAM ("additive") should be fit. |
| family | the distributional family from which to model response. Options are "beta", "binomial" (GLM only), "poisson", and "gamma". |
| intercept | a logical indicating whether an intercept is desired. Only applicable when model = "linear". Default is TRUE. |
| tol | the tolerance for convergence. Must be positive. Default is 1e-8. |
| max_iter | an integer specifying the maximum number of allowed iterations. Default is 100. |

Details

This is a function for training and fitting Generalized Linear Models (GLMs) and Generalized Additive Models (GAMs). It implements these models using Iterative Reweighted Least Squares (IRLS) described in Hastie and Tibshirani 1990 ([doi:10.1214/ss/1177013604](https://doi.org/10.1214/ss/1177013604)). This function supports Beta regression, Logistic regression, Poisson regression, and Gamma regression (Logistic GAMs are currently not supported).

Value

The output is a list containing:

| | |
|-----|---|
| eta | a vector of un-transformed fitted values. |
| mu | a vector of transformed fitted values. |

`num_iter` the number of iterations until convergence or timeout.

`dev` the convergence criteria achieved at the end.

`coef` a numeric vector of estimated coefficients (only applicable when `model = "linear"`).

Examples

```
# generate random inputs
set.seed(10)
n <- 200
X <- sort(runif(n))
# Beta GLM vs. GAM
Y <- (X - 0.5)^2 + 0.5 + rnorm(n, sd = 1e-1)
beta_glm <- glam(cbind(X, X^2), Y, model = "linear", family = "beta")
beta_gam <- glam(cbind(X, X^2), Y, model = "additive", family = "beta")
plot(X, Y, pch = 20, xlab = "X", ylab = "Y", main = "Beta Regression Example")
lines(X, beta_glm$mu, col = "red", lwd = 2)
lines(X, beta_gam$mu, col = "blue", lwd = 2)
legend("bottomright", legend = c("GLM", "GAM"), col = c("red", "blue"), lwd = 2)
```

Index

glam, 2